

Cash Drawer AQ 7000

● Features

- | | |
|---|---------------------------|
| Heavy-duty electronic drawer in grey meta | Front input slot and lock |
| For both RJ45 and RS232 systems | Adjustable internal space |
| RJ-12 | |



● Electrical Specifications

Interface	DB9F connector RS-232C at baud rates from 110 to 19200 Handshake, parity, data, stop bits : set at will.
Activation Data	Any ASCII letter, preferably U (55h)
Pulse Duration	300 ms typical
Status Detection	(Optional) Pin 1 – DCD or Pin 9 – RI (when AC adapter is used)
Blanking	Approximately 10 seconds of blanking after RS-232C active. During the blanking period the drawer cannot be opened, to avoid opening by spurious signal at system start.
Power Supply	12V 1.5A max

● Physical Specifications

Bill Tray	Heavy duty engineering plastic construction. Adjustable divider for 4 or 5 compartments. Spring loaded bill clip.
Coin Tray	Separate coin tray removable from the bill tray. Adjustable divider for up to 9 compartments.
Slip Deposit Slot	Front access slot for checks, credit card receipt or any paper. 16mm space below coin tray provides room for the slips.
Drawer Modes	Solenoid : Open by drive signal to the solenoid
	Lock : Mechanically locks the drawer
	Manual : Open by key
Dimensions	C410B : 410(W) x 425(L) x 90(H) mm C410BL : 410(W) x 480(L) x 90(H) mm C420B : 420(W) x 440(L) x 105(H) mm C420BL : 420(W) x 490(L) x 105(H) mm
Weight	C410B : 7.5 Kg net 8.5 Kg gross C410BL : 8 Kg net 9 Kg gross C420B : 9 Kg net 10 Kg gross C420BL : 10 Kg net 11 Kg gross
Color	Standard : Pearl white and black (Other OEM colors available)

AQsonic EUROPE

Polg. Ind. Navisur c/ Narciso n°1
 Valencina 41907 – Sevilla (Spain)

Tel : 34 955 999 672
 Fax : 34 955 999 909

Web site : www.aqsonic.com
 E-mail : aqsonic@aqsonic.com

AQsonic Asia

11. Ally 21, Ln 20, Dashing Rd.,
 Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C

Tel : 886 3 323 0268
 Fax : 886 3 323 0269

Web site : www.aculapos.com
 E-mail : sales@aculapos.com



AQsonic EUROPE

Polg. Ind. Navisur c/ Narciso n°1
Valencina 41907 – Sevilla (Spain)

Tel : 34 955 999 672
Fax : 34 955 999 909

Web site : www.aqsonic.com
E-mail : aqsonic@aqsonic.com

AQsonic Asia

11. Ally 21, Ln 20, Dashing Rd.,
Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C

Tel : 886 3 323 0268
Fax : 886 3 323 0269

Web site : www.aculapos.com
E-mail : sales@aculapos.com