



# MBi Series **Ultimate Performance & Mobility**

## Quick. Durable. Portable.



Small & Light -  
Yet Durable & Dependable



Top Cover Opening for  
Easy Media Loading



Large LCD display  
(802.11b/g model)



Large Operator  
Control Buttons



### Streamlined Features

- Light-Weight & Portable
- Drop Test
- IrDA
- USB (MB400/410i only)
- 802.11g Wireless
- Bluetooth Connectivity
- RS232 (Serial)

### Industry Verticals

- Government
- Law Enforcement
- Logistics
- Manufacturing
- Retail
- Transportation
- Utilities

### Industry Applications

- Mobile Printing
- Receipt Printing
- Price Marking
- Mark Down
- Specimen Labeling
- Shelf Labeling
- Route Accounting
- Point-of-Sale

# General Specifications

## MBi Series

MODEL		MB200i	MB400i	MB410i
<b>PRINTING SPECIFICATION</b>				
<b>Print Method</b>		Direct Thermal		
<b>Print Resolution</b>		203 dpi (8 dpmm)	203 dpi (8 dpmm)	305 dpi (12 dpmm)
<b>Print Speed</b>		Up to 4"/s (103 mm/s) at 16% printing coverage - Default Print Speed is 3"/s (75 mm/s)		
<b>Max. Print Area</b>		1.89" (48 mm) W x 6.3" (160 mm) L	4.09" (104 mm) W x 11.69" (297 mm) L	
<b>MEDIA SPECIFICATION</b>				
<b>Sensor Type</b>		Reflective Sensor (for use with pre-printed marks) - See-Through Sensor (for die-cut label with gap) Dispenser Sensor		
<b>Media Type</b>		Roll Die-Cut Label with Gap or Pre-Printed Label, Linerless Media, Continuous Receipt Paper		
<b>Media Size</b>	Width	1.1" - 2.2" (28 mm - 57.5 mm) <sup>1</sup>	2" - 4.49" (53 mm - 114 mm) <sup>1</sup>	
	Length	0.63" - 6.4" (16 mm - 163 mm) <sup>1</sup>	1.1" - 11.8" (28 mm - 300 mm) <sup>1</sup>	
	Thickness	0.003" - 0.007" (0.064 mm - 0.19 mm)		
	Roll Specs	Outer Diameter : 2.63" (67 mm) - Inner Diameter: 0.75" (19 mm) or 1" (25 mm) for standard labels, 0.4" (10 mm) coreless for receipt paper or 0.75" (19 mm) for linerless paper		
<b>FONT / SYMBOLOGIES</b>				
<b>Internal Fonts</b>		XU, XS, XM, XB, XL, OCR-A, OCR-B, CG Times and Triumvirate		
<b>Barcode Symbologies</b>	Linear	UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™		
	2-D	PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbology		
<b>INTERFACE CHARACTERISTICS</b>				
<b>Interface Options</b>		RS232C, Bluetooth, IrDA (Ver.1.2, Standard Protocol, IrCOMM (3-wire cooked)), 802.11b/g Wireless LAN (Supports WEP 64/128bit, WPA, WPA (PSK, 802.1x), and EAP)		
		USB		
<b>OPERATING CHARACTERISTICS</b>				
<b>Battery</b>		7.4 V (2400mAH) Lithium Ion	14.8V (1700mAH) Lithium Ion	
<b>Environment</b>	Operating	5° F – 122° F (-15° C – 50° C), 20%-80% RH, non-condensing 32° F – 122° F (0° C – 50° C), 20%-80% RH, non-condensing for 802.11g/b		
	Storage	-13° F – 140° F (-25° C – 60° C), 20%-80% RH, non-condensing		
<b>Regulatory Approvals</b>		FCC Class A, B, C, UL, CE, TÜV, CSA		
<b>Dimensions (w/ rubber boot)</b>		3.5" (88 mm) L x 5.03" (128 mm) W x 2.9" (73 mm) H	3.9" (99 mm) L x 8" (202 mm) W x 6.5" (165 mm) H	
<b>Weight (w/ rubber boot)</b>		0.9 lbs. (405 g) incl. battery pack		2 lbs. (910 g) incl. battery pack
<b>Drop Specification</b>		6 ft. (1.83 m) - flat sides of printer to concrete		5 ft. (1.5 m) - flat sides of printer to concrete
<b>OPTIONAL ACCESSORIES</b>				
<b>Optional Accessories</b>		Battery Charger (Single and Multi-Battery Capabilities), Spare Battery, AC Adapter, Serial to PC Cable, Optional Swivel Belt, Weather-Resistant Carrying Case <sup>2</sup> , Holster <sup>2</sup> , Optional Shoulder Strap		
		Shoulder Bag with Rain-Resistant cover <sup>2</sup> , Shoulder Strap and Belt Bag <sup>2</sup>		
<b>OPERATIONAL FEATURES</b>				
<b>Firmware Features</b>		Auto Power Save. Printer enters sleep mode when idle for 5 seconds. Printer will power off automatically when idle for another 5 minutes. (Programmable power off feature)		
<b>Self Diagnosis Tools</b>		Head Check, Battery Balance Check, Paper End, Head Open, Test Print, Over charge/discharge protection		

<sup>1</sup> includes backing liner <sup>2</sup> Non-booted Models

### SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273  
Phone: (704) 644-1650 Fax: (704) 644-1662  
E-mail: satosales@satoamerica.com

©2011 SATO America, Inc. All rights Reserved. Rev B • Specifications subject to change without notice • Any unauthorized reproduction of the contents of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.