PA692 Rugged Handheld Computer

Stay competitive

The PA692 is a rugged mobile computer that combines the latest 3.75G wireless communication and advanced performance to provide the best data communications in today's aggressive business environment. PA692 also offers field-based workers with a host of data collection tools and a comprehensive wireless communication platform, all in a compact, durable and ergonomic form factor.

Faster and more productive

Powered by industrial grade 1GHz TI AM3715 processor and runs on a flexible Windows Embedded Handheld 6.5 platform, PA692 delivers the faster performance in highly mobile environments. In addition to 512MB NAND Flash and 512 DDR SDRAM to boast ample internal memory, PA692 also supports microSD expansion with an additional 32GB of storage capacity for data-intensive applications.

Rugged design

Able to withstand multiple 5-foot drops to concrete and IP65-sealed against water and dust, the PA692 is an extremely rugged outside-the-four-walls device you can count on to perform under harsh conditions. This durable design mitigates device downtime that negatively impacts business critical applications. The PA692 features a comprehensive wireless platform that includes integrated GPS, Bluetooth, WiFi and 3.75G connectivity. The PA692's external antenna for WWAN and WLAN ensure excellent wireless connectivity and performance. Field mobile workers can easily access information and accelerate their workflow while they're on the go.

All-in-one Functionality

PA692 offers an integrated 1D / 2D scanning capability, as well as a HF and UHF RFID reader / writer, GPS, and a high resolution 5.0 megapixel digital camera, combining multiple functions in one compact size which reduces the cost to purchase different devices. Besides, featuring latest NFC communication, PA692 offers convenient short-range communication between electronic devices. It enhances the service levels in ticket tracking, identity asset management applications

Accessories and options

PA692 offers various model options and accessories to fit your needs. Complement your mobile solution with various communication and charging cradles, extended batteries, car kits and headsets - anything and everything you'll need to make the PA692 the ideal rugged handheld solution for your mobile workforce.

Main Features

- Windows Embedded Handheld 6.5 Professional and Classic platform
- Advanced performance with industrial grade 1GHz processor
- Latest 3.75G wireless communication, WiFi, GPS, Bluetooth, CCX4 certified
- Large 3.8" WVGA high resolution LCD
- Dual microphone designed for clear voice communication
- Rugged Construction: IP65 rated and 1.5M drop certified
- All-in-one Function: Built in 1D/2D scanner and HF/NFC/UHF RFID Reader









System Features

CPU TI AM3715 1GHz Memory 512MB Mobile DDR RAM 512MB NAND Flash os Windows Embedded Handheld 6.5 Professional and Classic Languages support English, Simp. Chinese, Traditional Chinese, Japanese, Spanish, German, French

Display

Transflective color 3.8" full WVGA with backlight 800 x 480 sunlight readable LCD

Camera / Photos / Video

5.0 megapixel autofocus camera with flash Unitech MPEG-4 video codec (VGA resolution)

Symbologies

1D Barcode Engine

UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCI, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba

2D Imager (optional)

1D codes Australian post, British post, Canedian post, Codabar, Code 11, Code 128, Code 39, Code 93, EAN 13, EAN 8, IATA 2 of 5, ITF, ISBT, Japanesepost, Kix code (nl), Korean post, Matrix 2 of 5, MSI, Planet code, Postnet, RSS expanded, RSS limited, RSS 14, UPC A, UPC E, UPC E1

2D codes Aztec, Codablock F, Code 49, Datamatrix, EAN-UCC, composite, Maxicode, Micro PDF417, PDF 417, QR code, Tcif lonked C39

RFID Reader (optional)

| HF/NFC | Frequency : 13.56MHz | |
|--------|---|--|
| | Tag Support : ISO15693, ISO14443A , ISO14443B | |
| | Support NFC | |
| UHF | ISO/IEC 18000-6C | |
| | EPCglobal Class 1 Gen 2 | |
| | Operating Frequency 840–960 MHz | |

Audio

Dual Microphone with Echo Cancelation and Noise reduction design 1W Speaker 3.5mm headset jack





Head Office Taipei

http://www.ute.com e-mail: info@hq.ute.com

Unitech America

Los Angeles e-mail: info@us.ute.com http://us.ute.com http://can.ute.com e-mail: info@can.ute.com Mexico http://latin.ute.com e-mail: info@latin.ute.com

Unitech Europe

Tilburg / Netherlands http://eu.ute.com e-mail: info@eu.ute.com



26-key Numeric keypad, Qwerty Keypad

Expansion Slot

microSD microSD slot with SDHC Support (up to 32GB)

PA692

Specifications

Communication

USB

| USB | USB 2.0 Client and Host | |
|-----------|---|--|
| WLAN | .AN IEEE 802.11 a/b/g/n CCX4 Compliance and WiFi certific | |
| Bluetooth | Bluetooth 2.1 + EDR with Bluetooth SIG certification | |
| WWAN | 3.75G Radio | |
| | UMTS / HSPA+, 3GPP release 6 / 7 | |
| | USA: | |
| | Dual Band UMTS/HSPA+ (850, 1900 MHz), Dual-Band GSM (850/1900 MHz) | |
| | | |
| | EU: | |
| | Dual Band UMTS/HSPA+ (900/2100 MHz), | |

Power Source

| Main Battery | 8.14 Watt-Hour 3.7V @2200 mAh |
|----------------|---|
| | 14.8 Watt- Hour 3.7V @4000 mAh |
| Backup Battery | Li-Coin battery Supports 2 hours backup |
| | |

Enclosure

Weight Dimension 390g(13.76 oz) with 2200mAh Battery 430g(15.17 oz) with 4000mAh Battery 17.7 cm (7 in) x 7.4 cm (2.9 in) x 4 cm (1.6 in) (Antenna length excluded)

Environmental

Operating temperature Storage temperature **Relative Humidity Drop Specification** Sealing

14°F to 122°F (-10°C to 50°C) -4°F to 140°F (-20°C to 60°C) 5% ~ 95% (non-condensing) 1.5m (5 feet) IP65

Software

Microsoft Visual Studio 2005/2008 Mobile SIP(VoIP) Auto Installer

 Notification LEDs, Vibrator

Mobile Device Management Software and Service

12 Manage

Software and configuration management, Asset tracking, remote diagnostics and performance measurement

Accessories

4-slot multi-bay Ethernet cradle 4-slot battery charger Field Installable Gun grip USB cradle with battery charger Ethernet cradle with battery charger Main battery (2200mAh, 4000mAh) USB communication and charging cable RS232 Communication cable AC adaptor Mono 3.5mm headset Car kit

Regulatory Approvals

CE, FCC, BSMI, VCCI, CCC, RoHS compliance

Unitech Japan Tokvo

http://jp.ute.com e-mail: info@jp.ute.com

Unitech Asia Pacific & Middle East

Taipei . http://apac.ute.com e-mail: info@apac.ute.com / info@india.ute.com http://mideast.ute.com e-mail: info@mideast.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com e-mail: info@cn.ute.com Taipei http://tw.ute.com e-mail: info@tw.ute.com



Specifications subject to change without notice. Copyright 2013 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.