

Code Ranger Bluetooth

Soluciones flexibles de impresión para el ambiente móvil

Code Ranger Bluetooth Las soluciones Cognitive se enorgullecen en presentar su nueva adición móvil inalámbrica a la familia de impresoras portátiles de la serie "Code Ranger". La impresora "Code Ranger" con Bluetooth permite que el trabajador móvil imprima etiquetas al instante, eliminando el alto costo de comunicación de largo alcance con cables. La tecnología de Bluetooth consume menos vida de batería que 802.11b, permitiendo la eficiencia de la fuente de poder y proporcionando una productividad más grande.

Características & Beneficios

- **Capacidad de transferencia de datos de un punto a otro en distancia corta**
- **Reducción de tiempo de perdida para trabajadores móviles gracias a la extensión de vida de la batería**
- **Solicitud de impresión sin cables incómodos o caros**



Especificaciones Técnicas

CARACTERÍSTICAS FÍSICAS	2" OD	3.125" OD
Dimensions (H x W x D)	5.5 x 3.6 x 3.5 inches 142 x 92 x 89 mm	6.8 x 3.6 x 4 inches 172 x 92 x 102 mm
Weight (with battery)	1.4 lbs 0.63 kg	1.525 lbs 0.69 kg
Drop Specification	Mil-STD-810F, Method 516.5, Procedure IV Transit Drop, dropping directly to concrete	

COMUNICACIONES

Type	Serial (R5232), Class 2 Bluetooth 1.2
------	---------------------------------------

BATERÍA

Type	NiMH 2100 mAh
------	---------------

CAPACIDAD DE MEDIA	2" OD or 3.125" OD label or receipt stock
--------------------	---

MEDIA

Max Width (2" OD)	2.40" (61mm)
Max Width (3.125" OD)	2.24" (57mm)
Indexing	Black bar, notch and gap

CÓDIGO DE BARRAS

Types Supported	21 standard barcodes, including: Add2, Add5, Codabar, Code39, Code128A/B/C, D2of5, I2of5, S2of5, EAN8/8+, EAN13/13+, EAN128, Maxicode, MSI/I1, PDF417, Postnet, UPCA/A+/E/E1
Rotations	0° or 90°

AMBIENTE DEL USUARIO

Operating Temperature	14° F to 122° F (-10° C to 50° C)
Storage Temperature	-4° F to 140° F (-20° C to 60° C)
Relative Humidity	10% to 95% non-condensing RH

IMPRESIÓN

Method	Direct Thermal
Width	(max) 1.89" (48mm)
Length	(max) 19" (483mm) at 203 dpi, 76" (1220mm) at 101 dpi
Speed	3.5 ips (101mm/sec)
Resolution	Selectable 203 or 101 dpi
Typical Printhead Life	1,000,000" (50.80km) Warranty to 500,000 inches

LETRAS & GRÁFICAS

Bitmap Fonts	7 sizes w/ up to 16x16 magnification, variable boldness & spacing
AGFA Fonts	Sans-serif font in 7 sizes, up to 16x16 magnification, variable spacing
Scalable Smooth Fonts	3 Ultra Fonts: smooth characters, variable size, boldness, italics, grayscale
Graphic Formats	PCX, BMP
Rotations	0°, 90°, 180°, 270°

MEMORIA

RAM	256 KB
Non-volatile FLASH	2MB

ACCESORIOS COMUNES

	Windows® drivers, Quick Start Guide, label design software, programmer's guide, belt clip, Cable strain relief
--	--

ACCESORIOS OPCIONALES

Fast Charger	1.5 hr full charge
Quadrapack	4-bay Charger 1.5 hr full charge
Special Models/Upgrades	linerless, peeler
Carrying Accessories	Rugged carrying case, shoulder strap, belt clip
Additional Languages	Kanji character set
Service	Annual service contracts