
CognitiveTPG A760 POS Hybrid Multifunction Printer

Receipt and Multi-ply Form Printing for Retail, Government, Banking, and Hospitality



CognitiveTPG invented the industry's first hybrid printers by combining thermal and impact printing into a single solution. The A760 provides an accurate and user-friendly way to validate checks and print on multi-part forms up to five plies thick. Designed with over thirty five years of retail POS experience, the A760 integrates fast and reliable thermal printing with the industry's widest impact print zone.



RS232 Serial and USB Interface Shown Above

- Sharp graphics and easy to read text with 203 dpi thermal print resolution
- 180 mm/sec print speed with monochrome printing
- Industry's widest impact print zone, ideal for large and hard back forms (one to five ply)
- Flat slip table for simple and easy form alignmentchecks, slip, forms, and full page documents
- Optional MICR
- Standard two-year warranty with optional extended warranty up to five years
- Multiple communication interfaces available
- Cross selling and branding opportunities with our receipt marketing software
- Includes emulations for popular wide-format hybrid printers including the A756, A758, 7156, and 7158





A760 POS Hybrid Multifunction Printer

PRODUCT HIGHLIGHTS

Fast Printing

With a monochrome print speed of 180 mm/sec, CognitiveTPG's A760 hybrid printers keep checkout lines moving.

Reliable Technology

The A760, with its wide, flat slip table, presents an accurate and user friendly platform to print on checks, slips, and multi-part forms. Plus the MICR reader has over 99% check read accuracy rates.

Maintenance Free and Flexible


Features such as CognitiveTPG's exclusive self-sharpening ceramic knife allow for long-lasting service with no scheduled maintenance. The A760 has a high compatibility rate, allowing it to fit into many legacy applications.

Designed for Lower Cost of Ownership

With highly integrated electronics, low energy activation paper, and built-in reliability these printers offer the lowest total cost of ownership.

Expanded Marketing and Customer Loyalty

CognitiveTPG's patented ReceiptWare™ marketing software transforms every receipt into a promotional opportunity. Add logos, watermarks, offer promotions, highlight sales and savings, run contests and surveys, promote your Facebook page, include your own QR code. The opportunities are endless.



TECHNICAL SPECIFICATIONS

	RECEIPT STATION	SLIP STATION
Print Method	Direct Thermal, 203 DPI	9-Pin Impact
Character Cell Size	13x24, 10x24	7x7
CPI	15, 6, 20.3	14, 17
Print Columns	44 & 56	66 & 80
Print Line Width	2.8 in. (72 mm)	4.75 in. (120 mm)

CHARACTER SETS & BARCODES

Resident Code Pages 437, 737, 850, 852, 857, 858, 860, 862, 863, 865, 866, 1251, 1252, and 1255

UPC-A, UPC-E, JAN8, JAN13 (EAN), Code 39, Code 93 Interleaved 2 of 5, Codabar, Code 128 Code 128 extended EAN 128 RSS OR PDE-417

Code 126, Code 126 extended, EAN 126, R55, QR, PDF-417		
FEATURES		
Printing Speed	Monochrome 59.3 LPS (180 mm/sec) 4.8 LPS (16	
	mm/sec); Two-color 29.6 LPS (100 mm/sec)	
Auto Cutter	Partial Cut	
Data Buffer	8K	
User Memory	Up to 2 MB: shared for graphics, logos, user defned	
	characters and user data storage	
Communication	Dual 9-pin RS-232/USB, 25-pin RS-232, and	
	Powered USB	
Power	24 VDC	
Option	MICR Reader (Integrated in slip station)	
MICR READER		
Character sets/fonts	E-13B and CMC-7, auto discriminate	
Check Read Rate	99% minimum	

Parsing Formats	E-13B only. Programmable to any format

THERMAL PAPER REQUIREMENTS

Paper Type Direct Thermal, POS Grade(s), Kanzaki P320 color

Paper Roll (W X D) 3.15 in. X 3.55 in. (80 mm X 90 mm)

IMPACT SLIP FORMS

 Size- Front insertion (L x W)
 2.68 in, X 2.00 in, (68 mm x 51 mm)

 Size- Side insertion (L x W)
 2.00 in, X 8.00 in, (51 mm x 204 mm)

 Document
 US (8.5" x 11") and EMEA (A4) page sizes

 Number of Plies
 1 - 5 ply multipart

 Paper Thickness
 0.0160 in, maximum (0.400 mm)

RELIABILITY

Thermal Print Mechanism
Auto Knife Cutter
Inpact Print Mechanism
Impact Print Mechanism
Impact Printhead
Imp

DIMENSIONS

Footprint (W"x D"xH") 6.5 in. X 11.4 in. X 6.6 in.
(165.10 mm X 289.56 mm X 167.64 mm)

Weight 11 lbs. (printer only)
14 lbs. (w/carton, pads, and included accessories)

PRINTER DRIVERS

OPOS for Windows XP, & Vista, JPOS for Linux & Windows, Windows Mini Drivers for XP, Vista, 7 & 8, RS-232 Emulation Driver for USB

CERTIFICATIONS

EMI: FCC, ICES-003, VCCI: Class A; CE, Austel: Class B, Safety: UL 1950, CSA 22.2 No.950, CE (EN60950), MITI (power supply)

