CognitiveTPG A776 COMPACT MULTIFUNCTION PRINTER


Validation and Receipt Printing in Retail, Grocery/Convenience, Government, and Healthcare



From the company that brought you the first thermal/impact hybrid transaction printer with integrated MICR and clam shell drop-in paper loading design, CognitiveTPG offers the retail market its hybrid printer model A776 with two-color/monochrome printing, graphic and image capability, and a small footprint (under 73 sq. in) that fits almost anywhere.

"Fast, Reliable and Compact"

- Fast, maintenance-free thermal receipt/journal printer
- Drop validation impact print station with superior paper handling
- Built in MICR reader with 99% plus accurate read rates
- Cross selling and branding opportunities with our receipt marketing software
- Multiple communication interfaces
- Small footprint allows for more space at the checkout station
- Highest knifelife in industry





A776 COMPACT MULTIFUNCTION PRINTER

PRODUCT HIGHLIGHTS

Maintenance-Free

The A776 requires no scheduled maintenance for years of trouble -free service, backed by a two-year quality guaranteed warranty. The receipt printer uses standard thermal paper rolls which drop in for easy replacement. The slip printer includes our "clean fingers" ribbon cassette which makes changing the impact ribbon a clean and fast process.

Expand Marketing and Customer Lovalty

CognitiveTPG's ReceiptWare marketing software and the A776 printer enables the user to create custom product promotions, holiday specials, coupons, and other attention grabbing and loyalty building features directly on the receipt.

Versatile Multifunctional Printer

By combining the thermal receipt with the impact slip printing, the A776 delivers fast, reliable printing in a small footprint. The A776 is ergonomically designed to guickly locate slip form for validation and endorsements of checks. The paper low indicator alerts the operator to replace the roll before it interrupts a transaction.



PRINTER DRIVERS

OPOS for Windows XP, & Vista, JPOS for Linux & Windows, Windows Mini Drivers for XP, Vista, 7 & 8, RS-232 Emulation Driver for USB

CERTIFICATIONS

EMC emissions: EN55022:1998 Class B ITE emission requirements (EU); FCC 47 CFR Part 15, Class B emissions requirements (USA), VCCI Class B ITE emissions requirements (Japan); AS/NZS 3548:2002/CISPR22 Class B ITE emission requirements (Australia); EMC Immunity: EN55024:1998/A1:2001 Information technology equipment (EU)

TECHNICAL SPECIFICATIONS

| | RECEIPT STATION | SLIP STATION | |
|-------------------------------------|---|---|--|
| Print Method | Direct Thermal, 203 DPI | 9-Pin Impact | |
| Character Cell Size | 13x24, 10x24 | 7x7, 12x7, 5x9 | |
| CPI | 15, 6, 20.3 | 13.9 & 16.8 | |
| Print Columns | 44 & 56 | 42 & 51 | |
| Print Line Width | 2.8 in. (72 mm) | 3.02 in. (76.8 mm) | |
| CHARACTER SETS & BAF | RCODES | | |
| Resident Code Pages 437, 7 | 37, 850, 852, 857, 858, 860, | 862, 863, 865, 866, | |
| 1251, 1252, and 1255 | | | |
| UPC-A, UPC-E, JAN8, JAN1 | 3 (EAN), Code 39,Code 93 Inte | rleaved 2 of 5, Codabar, | |
| Code 128, Code 128 exte | nded, EAN 128, RSS, QR, PDF-4 | 417 | |
| FEATURES | | | |
| Printing Speed | Monochrome 74.0 LPS (250 | mm/soc) / 8 PS (16 | |
| Frinking Speed | mm/sec); Two-color 27 LF | | |
| Auto Cutter | Partial Cut | | |
| Emulations Available | | Application compatible escape commands, TPG | |
| Emalationer Wallable | A756/A758, ColorPOS | | |
| Data Buffer | 8K | | |
| User Memory | Up to 2 MB: shared for graphics, logos, user defned | | |
| , | | characters and user data storage | |
| Communication | Dual 9-pin RS-232/USB, 25-pin RS-232, Ethernet, and | | |
| | Powered USB | | |
| Power | 24 VDC | | |
| Options | MICR Reader | | |
| MICR READER | | | |
| Character sets/fonts | E-13B and CMC-7, auto disc | riminate (Integrated in slip | |
| | station) | | |
| Check Read Rate | 99% minimum | | |
| Parsing Formats | E-13B only. Programmable t | o any format | |
| THERMAL PAPER REQUI | REMENTS | | |
| Paper Type | Direct Thermal, POS Grade(s) | | |
| Paper Roll (W X Dia.) | 3.15 in. X 3.27 in. (80 mm X 83 mm) | | |
| | | | |
| IMPACT SLIP FORMS | | 107.00) | |
| Size | 2.75 in. X 5.00 in. (69.85 mm x 127.00 mm) minimum | | |
| May Form Longth | front & side 11.00 in. (279.4 mm) | | |
| Max. Form Length Number of Plies | 1 - 4 ply multipart | | |
| Paper Thickness | 0.014 in. maximum (0.35 mm) | | |
| i aper mickness | 0.014 III. IIIdxiIIIdiii (0.00 III | 111/ | |
| RELIABILITY | | | |
| Thermal Print Mechanism | 216 KM paper (64 M lines) | monochrome | |
| | 216 KM two-color (57 M lin | | |
| Auto Knife Cutter | 2 million cuts | | |
| Impact Print Mechanism | 15 million lines | | |
| Impact Printhead | 200 million characters | | |
| MICR reader | 200,000 Reads | | |
| Warranty | 2 years | | |
| DIMENSIONS | | | |
| Footprint (W"x D"xH") | 6.5 in. X 11.4 in. X 6.6 in. | | |
| (165.10 mm X 289.56 mm X 167.64 mm) | | 57.64mm) | |
| Weight | 7 lbs. (printer only) | | |
| | 10.5 lbs. (w/carton, pads, and ir | cluded accessories) | |
| | | | |



CognitiveTPG LLC 950 Danby Road, Suite 200, Ithaca, NY 14850 Copyright 2014 CognitiveTPG. All Rights Reserved.