



EDISECUTE® XID 8300 Retransfer Printer

THE FLEXIBLE WAY FOR SMART CARD PERSONALIZATION

- Single- or double-sided retransfer printer with various optional modules
- · Modern, industrial design with very small footprint
- Electronic security locks to secure access to supplies and consumables
- Over-the-edge printing with glossy photo finish quality for great-looking cards with crisp, clear colors and flawless continuous tones
- · Fast throughput of up to 100 cards per hour
- Highest ribbon capacity and detachable card hopper for easy handling and continuous operation
- Convenient and simple front-loading of supplies with color-coded cartridge system
- Heavy-duty ART Retransfer Film for long-lasting durable cards
- Lifetime printhead warranty (using EDIsecure® materials)
- Accessories compartment for cleaning kits and other accessories
- Optional single- and double-sided lamination for more durability and security

The modular single-or double-sided *EDIsecure® XID* 8300 Retransfer Printer was developed for industrial needs, thus it is provided with various optional modules such as bend remedy, flipper, and encoding modules. Based on wealth on experience with *XID* Retransfer Technology, the printer is ready for plug and play inline encoding and lamination. With its compact size, the printer delivers the right combination of reliability, performance and affordability for printing durable and secure cards. It almost achieves offset printing quality, even on uneven surface of smart cards.

The XID 8300 prints on a variety of card materials including long-lasting, durable non-PVC cards such as ABS, PET, and Polycarbonate. The lockable, spacious card hopper stores up to 200 blank cards to secure an interrupt-free workflow. The user-friendly front-loading system with replaceable cartridges makes changing of supplies fast and simple.

The printer is ready to meet your individual requirements and can be equipped according to the customer needs. Optional magnetic stripe, IC contact and smart card encoding is possible for further demands on card functionality. Extend the life time and security of your cards by joining the printer with the *EDIsecure*® Inline Lamination Modules ILM-LS for single-sided lamination and ILM-DS for simultaneous dual side lamination.

Diverse security features such as electronic security lock, Kensington-lock, dye-sublimation UV ink ribbon for invisible security printing, IPSEC for encrypted data transfer through networks, and Security Erase of black data on used supplies help to secure the environment and cards from counterfeiting and to avoid misuse of personal information.

























FEATURES:

- Space saving internal installation of optional modules such as bend remedy, flipper, and encoding modules
- Electronic security locks (driver driven) for front door and card hopper for utmost security
- Printer Look-Up Tables and pre-selection of 5 different card type profiles
- Automatic ribbon detection and low ribbon warning
- Auto cleaning notification
- Removable cleaning roller unit for long-term usage and reliable, steady card cleaning
- Easy replacement of ink ribbons and Retransfer Film via front loading system
- Detachable card hopper for 200 cards
- Built-in operating panel with LCD for convenient set-up and
- Print head has no contact with card, minimizing risk of damage
- Accessories compartment for cleaning kits and other accessories
- Field upgradeable encoder options
- Intuitive, in-house developed printer driver for utmost user convenience and productivity
- USB 2.0 and Ethernet ports for easy connection with PC or network

SUPPLIES

- 4 Panel Color Ribbon (YMCK): 1,000 cards/ribbon
- 5 Panel Color Ribbon (YMCKK): 750 cards/ribbon
- 5 Panel UV Ribbon (YMCK-UV): 750 cards/ribbon (optional)
- 5 Panel Peel-Off Ribbon (YMCK-PO): 750 cards/ribbon (optional)
- XID ART Retransfer Film: 1,000 cards/film

OPTIONS

- Bend remedy station
- Magnetic stripe encoding (HiCo and LoCo)
- Contact and contactless chip encoding (Mifare, DESFire, HID iCLASS, Legic, etc.)
- A variety of chip encoder plug-ins for Advanced CEF
- Inline lamination, single- and double-sided (ILM-DS)

CONFIGURE YOUR CARD IDENTITY SYSTEM, ASK FOR:

- FDIsecure® Inline Lamination Modules
- EDIsecure® Card Management Software Suite
- *IDExpert®* Identity Management Solutions
- EDIsecure® Image Capture Modules
- EDIsecure® Image Enhancement Software
- EDIsecure® Card Materials

SPECIFICATIONS OF XID 8300

Print Method Dye-sublimation retransfer

Print Mode Single- or double-sided (optional)

over-the-edge retransfer printing

Up to 100 cards per hour (single-**Print Speed**

sided)

Print Resolution 300 dpi

Printhead Lifetime warranty

(using *EDIsecure*® materials)

Card Types PVC, Composite PVC, ABS, PET,

> and Polycarbonate Cards of ISO ID-1/CR-80 size, 85.60 x 53.98 mm

Card Thickness 0.25 - 1.02 mm (hopper adjuste-

ment required)

Input Hopper Capacity 200 cards (0.76 mm)

Output Hopper Capacity 100 cards (0.76 mm)

Interface USB 2.0 and Ethernet

Operating System Support Windows 2000, Windows XP,

Windows Vista, Windows 7

Printer Dimensions 343 x 322 x 360 mm (WxDxH)

Weight 13.9 kg (excluding optional

built-in items)

Power Supply 100/120 V and 220/240 V, 50/60 Hz

FCC, CE, UL, GOST-R, and CCC

approved

Operating Environment 15°C to 30°C, 35% to 70% non-

condensing humidity

Digital Identification Solutions AG

Phone: +49 711 341 689 - 0 Email: mail@digital-identification.com

Digital Identification Solutions Pte. Ltd. **Singapore 757718** Phone: + 65 6352 8364

Email: mail@sg.digital-identification.com

Digital Identification Solutions (Branch) Dubai, United Arab Emirates Phone: + 971 4 299 4146 mail@uae.digital-identification.com Digital Identification Solutions (Beijing) Co. Ltd. **P.R. China** Phone: +86 10 6437 4376

Digital Identification Solutions S. de R.L. de C.V.

Email: mail@cn.digital-identification.com

México Phone: + 52 442 2171 768 - 0

Email: mail@mx.digital-identification.com

Digital Identification Solutions LLC United States of America Phone: + 1 864 272 1199

Email: mail@us.digital-identification.com

vps ID Systems GmbH **Germany** Phone: +49 7243 5488 - 0

Email: info@vps.de