EPSON® TM-L90

Liner-free Compatible Label Printer



- Cost-effective liner-free label printing for QSRs and food service
- Uses NCR Sticky Media[™] liner-free adhesive labels
- Fast printing speeds of up to 170mm/second
- Top margin reduction can reduce label length by 5% or more
- Automatic media type and paper width detection
- Low power consumption

Epson's TM-L90 liner-free compatible label printer offers fast, cost-effective, liner-free label printing for food service where adhesive labels can help improve efficiency, order accuracy and customer satisfaction.

Ideal for QSRs and food service

The TM-L90 liner-free compatible label printer is ideal for food service applications where speed of service and order accuracy are critical to reducing operating costs and improving customer satisfaction. It also can be used as a thermal receipt printer when needed.

All the features you need

The TM-L90 liner-free label printer has all the features you need to print "stay stuck" labels quickly and easily. It prints labels at speeds up to 90mm per second and receipts up to 170mm per second at a crisp 203 x 203 dpi. It also supports variable length label output, and accepts 40mm or 80mm label and receipt rolls that are up to 4" in diameter.

Reduces material costs & waste

Epson's TM-L90 liner-free label printer features top margin reduction that can reduce the length of each label by 5% or more. And because the labels are liner-free it also eliminates the potential safety hazards and waste created by liners used on standard labels.

Liner-free label media

The TM-L90 liner-free label printer was designed specifically for use with the NCR Sticky Media™. Tested extensively in demanding food service environments, NCR Sticky Media has proven to be highly reliable and food safe.

Integration is easy

The TM-L90 liner-free label printer supports multiple interfaces including serial, parallel, Ethernet, USB and wireless, and is compatible with all major POS systems.

Features Epson reliability

With an MCBF of 70 million lines for receipts and 35 million lines for labels, plus a MTBF of 360,000 hours, the TM-L90 delivers the reliability customers expect from Epson.

Backed by the leader

The TM-L90 liner-free compatible label printer is backed by Epson's industry-leading service and support programs and comes with a one-year limited warranty.



Compact Thermal Printer for Liner-free Labels and Receipts

All the features you need

- Cost-effective liner-free label printing for QSRs and food service
- For use with NCR Sticky Media™ liner-free adhesive labels or thermal receipt printing
- Fast printing speeds up to 90mm/sec for labels and 170mm/sec for receipts
- Top margin reduction reduces media usage and waste
- Low power consumption
- One-year limited warranty

Printer

Print method Thermal line printing

Print speed 170mm/sec (thermal receipt); 90mm/sec (label media)

Print resolution 203 x 203 dpi

Print font

Font (A/B) 40mm: 12 x 24, 7 x 17 / 9 x 17, 7 x 17

80mm: TM-T88 compatible mode $13 \times 24 / 10 \times 17$;

TM-L90 compatible mode $12 \times 24 / 9 \times 17$

Column capacity 64/48 columns

Character size 1.13 x 2.13 / 1.5 x 3.0 / 1.0 x 2.0mm (W x H)

Character set 95 Alphanumeric, 37 International, 128 x 11 Graphic

Barcode UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), ITF,

CODE39, CODE93, CODE128, CODABAR, PDF417,

MAXICODE, QR CODE

Paper width 40mm or 80mm Paper diameter 4" (102mm)

Media thickness 2 mil to 8 mil, depending on media type

Reliability

MTBF 360,000 hours

MCBF 70 million lines (receipts), 35 million lines (labels)
Autocutter 2 million cuts (receipts), 1 million cuts (labels)

General information

Interfaces Universal Interface Board (UIB); provides access to

connections for Serial, Parallel, USB, Ethernet, Powered USB, Wireless

Data buffer 4K or 45 bytes
Power 24 VDC±7%
Power consumption Approx. 1.7A (mean)

D.K.D. function 2 drawers

Overall dimensions $203(H) \times 140(W) \times 148(D)mm (8.0" \times 5.5" \times 5.8")$

Mass Approx. 1.9 kg (4.18 lbs)

Color Epson Dark Gray (EDG), Epson Cool White (ECW)

Factory options PS-180 AC adaptor, paper roll spacer Operating systems Microsoft® Windows® 7, Vista, XP

Environmental standards WEEE, RoHS compliant

EMI standards VCCI class A, CE marking, Canada EMI, AS/NZS

3548

Safety standards UL, CSA, TÜV (EN60950)

Font emulation TM-T88 series (180 dpi), Ithaca (203 dpi) font

emulation available

Warranty One-year limited warranty



Inch values are approximate dpi: dots per 25.4mm (dots per inch) cpi: characters per 25.4mm (characters per inch) lps: lines per second











EPSON® EXCEED YOUR VISION

pos.epson.com/foodservice

 Product
 Features
 Model Number

 TM-L90-E03
 Ethernet, EDG**
 C31C412A8461

 TM-L90-P02
 Parallel, EDG**
 C31C414A8931

NCR Sticky Media™, 80mm***

 TM-L90-S01
 Serial RS232, EDG**
 C31C414A8911

 TM-L90-U04
 Powered USB, EDG**
 C31C414A8891

 TM-L90
 ECW, No UIB Interface**
 C31C412601

 NCR Sticky Media", 40mm***
 9023-1055

9023-0839

*Contact your Epson representative for additional models

**Includes AC adapter (PS-180-343)

Ordering information*

***For NCR Sticky Media™, visit http://www.ncr.com

Packaging specifications

Single box dimensions (L x W x H) $10.11'' \times 7.59'' \times 9.48''/257 \times 193 \times 241$ (mm) Units per pallet: AIR 6 units per layer, 5 layers = 30 units (pallet weight = 339kg) Units per pallet: OCEAN 6 units per layer, 7 layers = 42 units (pallet weight = 466kg)