

3870

Cordless Linear Imager



Features

Multiple Scanner Support - Each base unit supports up to nine scanners simultaneously. This increases productivity and flexibility without the added costs of additional bases and terminals.

Application Work Groups - Supports up to nine application work groups on a single base. This extremely powerful feature increases the number of jobs supported by a terminal, and allows you to easily adjust to changing workloads.

Broad Range Coverage - Scanner coverage of 31,400 square feet (2,919 square meters) increases mobility and productivity by allowing the scanner to be taken to the job, rather than taking the job to the scanner.

Eliminates Cables - Improves safety conditions by avoiding accidents and injury as a result of cables becoming entangled in equipment and machinery. Eliminates cable replacement costs.

Unique Charge Pack Design - Removable charge pack that is recharged simply by plugging into a wall outlet, then operates through the entire work day.

Rugged Design - Water and dust resistant to IP 54 rating.

State-of-the-Art Radio Technology - Two-way 2.4 GHz frequency hopping spread spectrum radio with forward error correction is robust against interference. Makes use of the license-free ISM band. Robust system delivers reliable and snappy, error-free communication.

The 3870 cordless scanner addresses the needs of many applications. It is designed for tough industrial use, such as on loading docks, where shipping and receiving of materials requires the freedom to move around, and industry standards recommend the use of linear bar codes and PDF417 codes on shipping labels. The cordless scanner is also ideal for manufacturing applications, such as work-in-process, where safety may be an issue. Eliminating the cables prevents the cord from getting entangled in machinery and equipment, thus avoiding the chance of an accident. Other applications include interfacing to RF LAN based terminals mounted on forklift trucks, tool crib management, asset tracking, inventory control, and point-of-sale terminals.

The 3870 joins a family of rugged and reliable cordless products, including the SCANTEAM® 2070 host interface base unit. The 3870PDF is designed for aggressive reading performance on PDF417 and MicroPDF417. The 3870HD reads high density bar codes with dimensions as small as 3 mil., while the 3870LX reads 15 mil. codes out to 18 inches. All these configurations feature an IP 54 sealed-enclosure rating and the industry's best drop specification for cordless scanners.

The 3870 features linear imaging technology in a cordless bar code reader. A bright, sharp aiming line and high-resolution imaging combine to deliver bar code reading performance that was previously only possible using a laser scanner.

The 3870 offers many advantages over a laser scanner. Its aiming line is brighter than a standard laser. It scans and decodes 270 times per second, about seven times faster than a laser. It can read all common linear bar codes, plus PDF417 and MicroPDF417. Thanks to onboard Flash memory, the reader can be easily upgraded when new features and new symbologies become available.

3870 Specifications

Optical Performance

Illumination:	630 nm Visible Red LED
Receiving Device:	3648 element linear imager
Skew Angle:	±30°
Pitch Angle:	±15°
Horizontal Velocity:	3 in. (7.6 cm) per second
Min. Reflective Difference:	30%
Scan Rate:	270 scans per second

Mechanical/Electrical

Dimensions	3870 Scanner	2070 Base
Weight:	16 oz. (448 g)	7.25 oz. (206 g) w/o cable
Height:	8.5 in. (21.6 cm)	1.4 in. (3.6 cm)
Power Requirements		
Input Voltage:	4 to 14 VDC	4 to 14 VDC
Current Draw		
Operating:	425 mA (typical) while scanning	325 mA (typical) @5 VDC
Standby:	30 mA	NA
Environmental		
Sealing:	IP 54 (Water and Dust Resistant)	IP 53 (Water and Dust Resistant)
Temperature		
Operating:	32° to 122°F (0° to 50°C)	-4 to 122°F (-20° to 50°C)
Storage:	-22° to 140°F (-30° to 60°C)	-40° to 158°F (-40° to 70°C)
Humidity:	0 to 95%, non condensing	0 to 95%, non condensing
Mechanical Shock:	Functional after 26 drops from 6 ft. (1.8 m)	Functional after 26 drops from 4 ft. (1.2 m)
Ambient Illumination:	0-100,000 lux	NA
ESD Protection:	Functional after 15 kV discharge	

Radio

Frequency:	2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Spread Spectrum
Range:	100 ft. (30 m) typical
Data Rates:	1 Mbps

Charge Pack

	Nickel Metal Hydride (NiMH) battery
Input Voltage:	120 V/240 V, 50 Hz/60 Hz
Capacity:	1200 mAh
Number of Scans:	18,000
Expected Hours of Operation:	25 hours @ 1 scan every 5 seconds
Charge Time at 120 Vac:	6 hours for full charge from full discharge

Symbologies

Symbologies Supported:	Codabar, Code 39, Code 128, ISBT 128, UPC/UPC-E, EAN/JAN, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 93, Code 11, ISBN, Telepen, and Reduced Space Symbology (RSS). 3870PDF: PDF417, MicroPDF417, and EAN•UCC Composite Symbology.
-------------------------------	--

Warranty

Three year factory warranty

Agency Conformance

Consult your Hand Held Products Customer Account Representative for specific country agency

Electromagnetic Emissions/Immunity	Safety	RF Approvals
USA: FCC Part 15, Class B Canada: SOR 88/475 Class B Europe: EN 55022 (CISPR22) Class B, EN 61000-3-2 & -3, ETS 300 826 Other: EMC 89/336/EEC, EN 50082-1:1992, IEC 801-2:1991, IEC 801-3:1984, IEC 801-4:1988	USA: UL listed, C22.2 No 950/UL 1950 Canada: cUL Listed Europe: TUV Rheinland GS Licensed EN 60950 (IEC950) Australia: AS/NZS 3548	USA: FCC Part 15.249 Canada: RSS 210 Europe: ETS 300 328

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France
Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com
Shanghai
Tel: +86 21 6361 3818
appresales@handheld.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 2178 0500
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2178 0500
lapresales@handheld.com
Mexico
Tel: +52 55 5203 2100
lapresales@handheld.com

Web Site Address www.handheld.com
Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.