## OMNIKEY<sup>®</sup> 6321 CLi USB Reader

Contactless USB Smart Card Reader

- Versatile Applications Ideal for mobile end-user environments using contactless HID iCLASS<sup>®</sup> technology
- Fast Contactless Transmission Supports fastest ISO standard transmission modes
- Designed for User Convenience Housing design is optimized for advanced contactless applications
- Readily compliant Seamless integration with iCLASS on the Desktop<sup>™</sup> and other applications

## **SECURE** identification.

The OMNIKEY® 6321 CLi USB smart card reader represents the ideal contactless HID iCLASS® reader in a convenient dongle-size device. Reading and writing to any contactless HID iCLASS card, the device economically supports mobile end-user environments where contactless smart card technologies are used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY 6321 CLi allows users to experience the convenience, speed and security of HID iCLASS contactless technology for applications such as iCLASS on the Desktop<sup>™</sup>.

The OMNIKEY 6321 series readers work seamlessly with iCLASS-enabled logical access applications in combination with naviGO<sup>™</sup>, a cost-effective solution that simplifies deployment of strong authentication, managing and automating the lifecycle of strong authentication user credentials on iCLASS smart cards. Designed to enable iCLASS on the Desktop applications, naviGO allows card holders to manage their own enrollment, PIN management and knowledge-based authentication through a self-service browser based application.

- Features host interface USB 2.0 and is compliant with USB 1.1
- Compliant with all relevant safety and environmental standards, including CE, FCC, UL, RoHS and WEEE

For actual driver downloads please visit www.hidglobal.com/omnikey



## **Specifications**

Base Model Number	OMNIKEY® 6321 CLi
Dimensions	3.7" x 1.02" x 0.59" (94 x 26 x 15mm)
Weight	Approx. 0.59 oz. (17 g.)
Power supply	Bus powered
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10 - 90% rH
- For mun8	HOST INTERFACE
Host Interface	USB 2.0 (also compliant with USB 1.1)
Transmission speed	I 2 Mbps (USB 2.0 full speed)
Transmission speed	
Protocols	HID ICLASS®
Protocols	
Driver Support	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Windows® XP 64bit, Windows® Vista (32bit / 64bit), Windows 7 (32bit / 64bit), Linux® and Mac® OS X
Status indicator	Blue color LED (blue=ready, blinking=busy)
Color	Grey-Blue
Options	Customer Specific Logo and Colors: Available upon request
Composition	ABS
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL', USB 2.0 (USB 1.1 compatible)
Safety / Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two (2) year manufacturer's warranty. (For drivers, see complete lifetime support policy.)
	I = Windows® Hardware Quality Lab
	Wash suming Image being Comparable with functions Image being Ima



**ACCESS** experience.

HID Global Offices:

Corporate North America 15370 Barranca Pkwy Irvine, CA 92618 U.S.A. Tel: 1 800 237 776 Tel: + 1 949 732 200 Fax: + 1 949 732 236

... | 800 237 7769 +| 949 732 2000 +| 949 732 2360

Asia Pacific 19/F 625 King's Road North Point Island East Hong Kong Tel: +852 3160 9800 Fax: +852 3160 4809

Latin America Circunvalación Ote. #201 B Despacho 2 Col. Jardines del Moral Leon 37160, Gto. Mexico Tel: +52 477 779 1492 Fax: +52 477 779 1493

Europe, Middle East & Africa Haverhill Business Park Phoenix Road Haverhill, Suffolk CB9 7AE England Tel: +44 1440 714 850 Fax: +44 1440 714 840

ASSA ABLOY

© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

MKT-OMNIKEY\_6321CLi\_DS\_EN Rev. 07/2010 hidglobal.com