

# MC3000 Family



#### **FEATURES**

Light, ergonomic design Reduces user fatigue for higher productivity in scan-intensive applications

### Well-balanced brick or gun form factors

Comfortable to use in intensive scan environments for prolonged periods

#### Visual scanning feedback on the sides (gun only) Provides visual in addition to audio feedback without

having to reorient the device

#### Laser versions with adjustable rotating scan turret with left, right and front positions

User can adjust the scanning positions for maximum comfort and productivity

### 320 x 320 resolution color/mono display (with backlight)

30% higher resolution than 1/4 VGA allows easy viewing in many environments for increased accuracy

### Capture, move and manage data in real time for real business value

The MC3000 mobile computers from Motorola are rugged mobile computers ideal for scan-intensive environments that require high-quality data capture throughout the enterprise. Their superior ergonomic design and balance help to facilitate faster decision making and increased workforce satisfaction inside the retail store, on the loading dock or on a delivery route.

## Unprecedented flexibility, performance and power

A variety of feature options, including: color display; batch or wireless communications: brick or gun form factor; Bluetooth and audio capability; three keypad options; and the ability to capture images, scan bar codes, or read DPM marks, allowing you to meet your customer, employee and IT needs. Each MC3000 mobile computer is based on a highperformance mobile Intel XScale PXA270 processor supporting up to 128MB RAM, which helps you gain significant business value by ensuring maximum user productivity.

The Microsoft Windows CE and Windows Mobile operating systems offer familiar interfaces and the power of Web-based applications for greater usability and employee satisfaction.

### **Reliable performance in variable conditions**

The MC3000s' rugged design and IP54-rated sealing ensure continued use and uptime by protecting against dust, moisture and extreme

temperatures. And, whether working inside or out, the MC3000s have a drop spec of four feet to concrete across a wide temperature range, reducing equipment and maintenance costs.

### Unlock the value of your information with Microsoft Windows CE or Windows Mobile

Bringing the next generation of mobile computing to your business, Motorola's MC3000s are built on the Windows CE or Windows Mobile operating systems. With real-time processing, faster performance, rich multimedia and Web browsing capabilities, your enterprise can become truly mobile with interoperability between personal computers, servers, Web services and devices. Motorola's enterprise mobility solutions go beyond mobile devices and wireless connectivity to ensure that every aspect of your mobility solution works seamlessly and at maximum efficiency.

### Complete your solution with Motorola Global Services

Even the most rugged products require a maintenance plan and support strategy. That's why Motorola has designed comprehensive set of services that cover every aspect of the MC3000s — helping to ensure our customers derive full value from their investment.

For more information, access our global contact directory at www.motorola.com/customersupport. jsp or visit us on the web at www.motorola.com/ mc3000.

MC3000 Family

### Wireless 802.11b/g/a LAN connectivity

Provides real-time data exchange for maximum productivity

### Bluetooth option

Enables use of and wireless connection to a range of devices

#### IP54-rated sealing

Protects against water and dust for reliable performance in rough environmental conditions

### Intel XScale PXA270 processor and Microsoft Windows CE or Windows Mobile operating systems

Delivers high-speed CPU performance through familiar interfaces with wide software application support

#### Device management with Mobility Services Platform (MSP)

Enables real-time monitoring of critical mobile computer and wireless infrastructure parameters

## MC3000 Series Specifications

Physical Charac	teristics		
Dimensions			
Brick/Imager Configuration:	7.43 in. L x 3.18 in. (188 mm x 80.8 m At grip: 2.40 in. W (61 mm x 36.3 mm	m x 44.7 mm) x 1.43 in. D	
Brick/Laser Configuration:	8.33 in. L x 3.18 in. (211.6 mm x 80.8 n At grip: 2.40 in. W (61 mm x 27.9 mm	nm x 39.9 mm) x 1.10 in. D	
Gun Configuratio	ons: 193 L x 80.8 W x 1	66H mm	
Weight			
Brick/Laser confi	g.: 13.4 oz. (379 gm) (	13.4 oz. (379 gm) (with WLAN)	
Brick/Imager con	fig.: 15.1 oz. (428 gm) (	15.1 oz. (428 gm) (with WLAN)	
Gun Configuratio	ons 18.59 oz. (527 gm) with Blueooth)	(19.6 oz./555 gm	
Performance Ch	aracteristics		
	Monochrome Display Configuration	Color Display Configuration	
Display Res.:	320 x 320	320 × 320	
Operating System:	MC3090: Microsoft Windows CE 5.0	MC3090: Microsoft Windows CE 5.0 or Windows Mobile 6.1	
App Dev.:	Motorola SDK	Motorola SDK	
Environment:	Microsoft Windows CE SDK	Microsoft Windows CE SDK or Windows Mobile SDK	
Processor:	IntelXScale PXA270 @312MHz	IntelXScale PXA270 @520MHz	
Memory: RAM/Flash	32MB/64MB	64MB/64MB or 128MB/64MB or 128MB/1GB	
Data Capture Options:	1D Laser: reads 1D bar codes 2D Imager: reads 1D and 2D bar codes omni-directionally DPM Imager: reads data matrix marks, applied by dot peening, laser etching, molding, stamping or casting methods to multiple substrates including metal, plastic, or glass		
Secure Digital Slot:		ser accessible (located under battery)– oproved for memory expansion only	
Communications	:: RS232, USB (Host and	l Client)	
Power:	Brick/Laser Config. Brick/Imager Config. Gun Configurations	2,600 mAh @ 3.7Vdc 4,400 mAh @ 3.7Vdc 4,400 mAh @ 3.7Vdc	

Motorola Spectrum24, 802.11a, 802.11b,

802.11g; note: 802.11a not available in

Thailand.

Output Power:	100 mW U.S. and international	
Data Rate:	802.11b – 11 MB per second 802.11g – 54 MB per second 802.11a – 54 MB per second	
Antenna :	Internal	
Frequency Range:	Country-dependent; typically 2.4 to 2.5 GHz for 802.11b/g and 5.15 to 5.825 GHz for 802.11a	
Bluetooth:	Theatre dependent	
VOIP-ready (Class 2):	Optional (theatre dependent)	
User Environment		
Operating Temperature:	Monochrome: -4° to 122°F (-20° to 50°C) Color: 14° to 122°F (-10° to 50°C)	
Storage Temp:	-22° to 160°F (-30° to 70°C)	
Batt. Charging Temp:	32° to -40°F (0° to -40°C)	
Humidity:	5% to 95% non-condensing	
Drop Spec:	Multiple 4-foot (1.2-m) drops to concrete across operating temperature	
Tumble Spec:	500 one-half meter tumbles at room temperature (1,000 drops)	
Sealing:	IP54 Category 2	
Electrostatic Discharge (ESD):	+/-15kVDC air discharge +/-8kVDC direct discharge +/-8kVDC indirect discharge	
Peripherals and Acc	essories	
Cradles:	Single-slot USB/RS232 charging cradle with spare battery well	
Chargers:	Four-slot battery charger Adaptor for universal battery charger	
Printers:	Support Motorola approved printers	
Other Accessories:	Holsters, charging cables, magnetic strip reader	
Regulatory		
Electrical Safety:	Certified to UL60950, CSA C22.2No. 60950, EN60950/IEC 950	
EMI/RFI Radio Versions:	North America: FCC Part 2 (SAR), FCC Part 15, RSS210 Class B, EN 301 489-1, 489-17	
EMI/RFI Batch Versions:	EU: EN55022 Class B EN55024 Japan: CISPR 22, Class B Australia: AS3548 North America: FCC Part 15, ICES 003 Class B	
Laser Safety:	IEC Class 2/FDA Class II in accordance with IEC60825-1/EN60825-1	

## **€**N410 (€







motorola.com

WLAN:

Part number SS-MC3000. Printed in USA 08/08. MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. Symbol is a registered trademark of Symbol Technologies, Inc. All other product or service names are the property of their respective owners. @Motorola, Inc. 2008. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.