



MS210 CCD Scanner



Features

- Superior contact scanning
- Reads most commonly used bar code symbologies
- Hands-free operation for retail applications
- Replaceable interface cable
- Easy to use and configure
- Reads damaged labels
- Advanced Data Editing features
- Solid-state technology
- Supports multiple interfaces
- Low power consumption

The MS210 barcode scanner is a reliable, low cost bar code reader suitable for a wide range of environments. Its features and price make it the best solution for retail, medical and light industrial applications.

Extensive interface support

The MS210-1 flexible, multiple interface design supports keyboard wedge, RS232, USB, wand emulation and sixteen popular terminals by simply replacing the cable. This feature also prevents downtime caused by damaged cables. In addition, the IBM PC XT/AT keyboard wedge interface supports 8 different character sets.

Feature rich

The powerful built-in decoder reads and discriminates all major symbologies, reducing processing time and labor costs, while increasing accuracy. The decoder also allows editing and modifying scanned data before sending it to the host device.

Barcode menus provide extensive configuration options. The settings can then be cloned to other readers through the use of custom bar code labels.

Sleek, solid construction

The ergonomic design makes the scanning process easier and more comfortable. Aside from good looks, it is also rugged enough to withstand multiple six-foot drops to concrete.

The MS210 is manufactured at our ISO 9001 certified factory and comes with a 3-year warranty.

MS210 Specifications

Optical

Light source: 660 nm visible red LED
Sensor: 2,088-element linear array
Scan rate: 45 scans per second
Print contrast: 45% absolute dark/light reflectance at 660 nm
Scanning width: 3.15" (80 mm) at contact, 4.7" (120 mm) maximum
Resolution: 4 mils (0.1 mm) minimum
Depth of field: 1" (25.4 mm)

Decoder

Symbologies: UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCII, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba, EAN 128, Label Code IV, V and China Postal Code.
Operation modes: Trigger, flash, multiscan and continuous modes
Data editing: Preamble, postamble, code id and reformatting data
Function keys: PC, Macintosh and IBM terminal keyboard
LED: Two-color LED provides good read feedback
Buzzer: Provides additional audio feedback

Electrical

Operating voltage: +3.3 to 5 V DC
Consumption: 20 mA standby, 85 mA operating
EMI protection: CE approved, complies with FCC Class A

Mechanical

Length: 7.4" (190 mm)
Width: 3.46" (88 mm)
Height: 3.15" (50 mm)
Weight: 4.4 oz. (125 g) without cable
Shock: Withstands multiple 6 ft. (1.8 m) drops to concrete floor

Environmental

Operating Temperature: 32° to 122° F (0° to 50° C)
Storage Temperature: -4° to 140° F (-20° to 60° C)
Humidity: 20 to 95% RH non-condensing

Accessories

CCD Holder
Interface cables

Ordering Information

MS210-A	Keyboard wedge PC XT/AT (DIN connector)
MS210-P	Keyboard wedge PS/2 (miniDIN connector)
MS210-U	USB
MS210-R	RS232 (includes 5V AC adapter)
MS210-W	Wand emulation

Also supports Macintosh (ADB port), IBM, DEC, Dorio, Decision Data and other popular terminals.

www.unitech-adc.com



Unitech America
3700 Industry Ave. No 103
Lakewood, CA 90712
U.S.A.
Phone: 1-800-861-8648
Fax: 1-562-490-0320
www.unitech-adc.com
sales@unitech-adc.com

Unitech Europe
Ringbaan Noord 91
5046 AA Tilburg
The Netherlands
Phone: +31-13-460-9292
Fax: +31-13-460-9293
unitech-europe@wxs.nl

Unitech Electronics
3 Fl., No. 5, Alley 6, Lane 235
Pao Chiao Rd, Hsin-Tien City
Taipei Hsien, Taiwan, R.O.C.
Phone: +886-2-2918-2657
Fax: +886-2-2917-1474
aidcsales@unitech.com.tw